

## Battery Clamp Grease

### Description

Battery Clamp Grease is a special grease which is compatible with plastics and is formulated for the maintenance and care of motor vehicle electronic systems, particularly the battery terminals and electrical connectors.

### Properties

- prevents leakage currents
- reduces contact resistance
- good corrosion protection
- very compatible with plastics
- good electronic properties

### Technical data

Viscosity at 40 °C	70 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	8,5 mm <sup>2</sup> /s ASTM D 7042-04
Flash point	200 °C DIN ISO 2592
Pour point	-21 °C DIN ISO 3016
Worked penetration	265-295 1/10 mm DIN ISO 2137
Dropping point	90 °C DIN ISO 2176
Oil separation after 7 days at 40 °C	3,6 % DIN 51817
Oil separation after 18 hours at 40 °C	1,1 % DIN 51817
Flow pressure at -30 °C	<1400 mbar DIN 51805
Emcor corrosion class	0/0 DIN 51802
Copper corrosion after 24 hours at 100 °C	1 a DIN 51811
Behavior in the presence of water	0-40 DIN 51807 Teil 1
NLGI number	2 DIN 51818
Brief description	M2C-30 DIN 51502

### Areas of application

Used especially for battery terminals, connections and plug connectors in vehicle electronic system.

### Application

Clean contaminated components and treat with Battery Clamp Grease.



### Available pack sizes

10 g Cushion plastic	3139 D
10 g Cushion plastic	8045 RUS
50 g Tube plastic	3140 D-GB-E
50 g Tube plastic	7643 D-RUS
1 kg Can sheet metal	3142

**Our information is based on thorough research and may be considered reliable, although not legally binding.**